

# K624i

PROFESSIONAL CHOICE FOR LONG DISTANCES



## PRODUCT HIGHLIGHTS



- Wide field of view, exceptionally comfortable eyepiece and high contrast image
- Precise, clearly defined click mechanism and reliable repeat accuracy
- Optional left or right side windage
- Parallax wheel integrated into the elevation turret (patented) (50 m to  $\infty$ )
- Precise illuminated reticles in 1 st focal plane

The K624i sets standards in handling and ergonomics thanks to the unique arrangement of its operating elements. It offers outstanding optical performance, mechanical perfection and a unique range of well proven reticles for professionals and competition shooters.

## TECHNICAL DATA

<b>Magnification:</b>	6 - 24
<b>Objective lens diameter:</b>	56 mm
<b>Eye relief:</b>	90 mm
<b>Field of view:</b>	6.8 - 1.7 m/100 m
<b>Diopter compensation:</b>	+2 / -3.5 dpt
<b>Twilight factor (DIN 58388):</b>	18.3 - 36.7
<b>Adjustment range (E/W):</b>	2.5/1.1 m/100 m
<b>Parallax adjustment:</b>	50 m till $\infty$
<b>Tube diameter:</b>	34 mm
<b>Length:</b>	405 mm
<b>Weight:</b>	950 g
<b>Focal plane:</b>	1
<b>Illuminated:</b>	Ja
<b>Warranty:</b>	10 years

## FEATURES



1st focal plane



Main tube 34 mm



Adjustment direction  
CW or CCW



Windage left or right




Zero Stop




MIL


## RETICLES / SUBTENSIONS




MSR/Ki




Mil3




Mil4




SKMR



SKMR3



AMR



MOAK