

K16i

FAST TARGET ACQUISITION IN TOUGHEST ENVIRONMENTS



PRODUCT HIGHLIGHTS




- Sporty riflescope with ultra-wide field of view for fast target acquisition
- Developed for even the toughest demands
- Extra bright day illuminated reticles in the second focal plane
- 3GR reticle for IPSC and 3 Gun

The K16i is ideal for acquiring targets within a very short time thanks to its ultra-wide field of view. Competition shooters benefit from the extra-high nose and the large, easy to use adjustment ring.

TECHNICAL DATA

Magnification:	1 - 6
Objective lens diameter:	24 mm
Eye relief:	95 mm
Field of view:	42.3 - 6.7 m/100 m
Diopter compensation:	+2 / -3.5 dpt
Twilight factor (DIN 58388):	3.1 - 12.0
Impact correction per click:	.1 MRAD
Adjustment range (E/W):	2.2 / 2.2 m
Parallax adjustment:	100 m
Tube diameter:	30 mm
Length:	278 mm
Weight:	480 g
Focal plane:	2
Illuminated:	Ja
Warranty:	10 years

FEATURES



2nd focal plane




Main tube 30 mm



Adjustment direction
CW




MIL




Windage right


RETICLES / SUBTENSIONS



3GR



SM1



SI1